

Эргономика

- / В рабочей зоне оператора предусмотрено просторное место для ног с удобно расположенными педалями, что способствует комфортной работе водителя.
- / Простая и понятная приборная панель.
- / Гидравлические рычаги обеспечивают легкий доступ в сервисный отсек с любой стороны.
- / Регулируемые руль и сиденье позволяют оператору любой комплекции занять удобное рабочее положение.



Maneuverability

- / Drive to the rear steering wheel gives safe truck operation in confined spaces. The turning angle of rear wheel is upto 90 degree, compared with the same load capacity 4 pivot trucks, the turning radius is smaller about 400 to 450mm.
- / Driving speed is automatically reduction during cornering.



Reliability

- / AC motor is the simple brushless motor, less maintenance and better suitability for wet & explosive conditions.
- / Maintenance is easy and low-cost.

Side battery change

- / 24V battery is ideal for two or three shifts requirements, and side battery change is a perfect option to change the batteries quickly.



ВАШ поставщик HANGCHA

Торговый Дом "Вертикаль"

Центральный офис

г. Нижний Новгород, ул. Монастырка, д. 21Б
Тел.: 8 (800) 700-100-9 - звонки по России бесплатно
Тел.: 8 (831) 256-17-17 – многоканальный
info@td-v.ru
www.td-v.ru



Трехколесные электропогрузчики

Задний привод, серия А

грузоподъемность от 1 500 кг

A series 3-pivot Rear Drive Electric Forklift

A series 1.5t rear-wheel driving three pivot electric forklift truck is very suitable for operating in limited space, with small turning radius, which is the ideal forklift truck in store, supermarket and warehouse, etc.

Standard specification

- / Solid tyre
- / Emergency disconnect switch
- / Full suspension seat
- / Drive, lift, steering controlled
- / Self-diagnose system
- / 2 spools valves
- / 3m wide view mast
- / Adjustable steering wheel
- / Multi-function LCD display and trucklighting system
- / Rear view mirror
- / Tool box
- / Side battery change

Options

- / Drive wheel with Pneu tyres
- / 3 or 4 spools control valves
- / 4.3-6m full free triplex mast
- / 2.5-4.5m full free duplex mast
- / Different length forks
- / Attachments
- / Different load backrest

